

Product Specification

XBLW SN74HC245

Octal Bus Transceiver; 3-state

WEB | www.xinboleic.com




Description


The SN74HC245 is a 8-bit transceiver with 3-state outputs. The device features an output enable ($\overline{OE}$) and send/receive (DIR) for direction control. A HIGH on $\overline{OE}$ causes the outputs to assume a high-impedance OFF-state. Inputs include clamp diodes. This enables the use of current limiting resistors to interface inputs to voltages in excess of V_{CC} .

Features


- Octal bidirectional bus interface
- Non-inverting 3-state outputs
- Specified from -40°C to +125°C
- Packaging information: DIP-20/SOP-20/TSSOP-20/SOIC-20-208mil




DIP-20



SOIC-20-208mil



SOP-20



TSSOP-20

Ordering Information

Product Model	Package Type	Marking	Packing	Packing Qty
XBLW SN74HC245N	DIP-20	74HC245N	Tube	720Pcs/Box
XBLW SN74HC245DTR	SOP-20	74HC245	Tape	2000Pcs/Reel
XBLW SN74HC245TDTR	TSSOP-20	74HC245	Tape	2000Pcs/Reel
XBLW SN74HC245NSDTR	SOIC-20-208mil	74HC245	Tape	2000Pcs/Reel

Block Diagram




Figure 1. Logic symbol





Figure 2. IEC logic symbol

Pin Configurations



Pin Description

Pin No.	Pin Name	Description
1	DIR	direction control
2	A0	data input/output
3	A1	data input/output
4	A2	data input/output
5	A3	data input/output
6	A4	data input/output
7	A5	data input/output
8	A6	data input/output
9	A7	data input/output
10	GND	ground (0V)
11	B7	data input/output
12	B6	data input/output
13	B5	data input/output
14	B4	data input/output
15	B3	data input/output
16	B2	data input/output
17	B1	data input/output
18	B0	data input/output
19	OE	output enable input (active LOW)
20	V _{CC}	supply voltage

Function Table

Input		Output	
OĒ	DIR	An	Bn
L	L	A=B	input
L	H	input	B=A
H	X	Z	Z

Note: H=HIGH voltage level; L=LOW voltage level; X=don't care; Z=high-impedance OFF-state.

Electrical Parameter

Absolute Maximum Ratings

(Voltages are referenced to GND(ground=0V), unless otherwise specified.)

Parameter	Symbol	Conditions		Min.	Max.	Unit
supply voltage	V _{CC}	-		-0.5	+7.0	V
input clamping current	I _{IK}	V _I < -0.5V or V _I > V _{CC} +0.5V		-	±20	mA
output clamping current	I _{OK}	V _O < -0.5V or V _O > V _{CC} +0.5V		-	±20	mA
output current	I _O	-0.5V < V _O < V _{CC} +0.5V		-	±35	mA
supply current	I _{CC}	-		-	70	mA
ground current	I _{GND}	-		-70	-	mA
storage temperature	T _{stg}	-		-65	+150	°C
total power dissipation	P _{tot}	-		-	500	mW
soldering temperature	T _L	10s	DIP	245		°C
			SOP/TSSOP/DHVQFN	260		°C

Recommended Operating Conditions

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
supply voltage	V _{CC}	-	2.0	5.0	6.0	V
input voltage	V _I	-	0	-	V _{CC}	V
output voltage	V _O	-	0	-	V _{CC}	V
input transition rise and fall rate	Δt/ΔV	V _{CC} =2.0V	-	-	625	ns/V
		V _{CC} =4.5V	-	1.67	139	ns/V
		V _{CC} =6.0V	-	-	83	ns/V
ambient temperature	T _{amb}	-	-40	-	+125	°C

Electrical Characteristics

DC Characteristics 1

($T_{amb}=25^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
HIGH-level input voltage	V _{IH}	V _{CC} =2.0V		1.5	1.2	-	V
		V _{CC} =4.5V		3.15	2.4	-	V
		V _{CC} =6.0V		4.2	3.2	-	V
LOW-level input voltage	V _{IL}	V _{CC} =2.0V		-	0.8	0.5	V
		V _{CC} =4.5V		-	2.1	1.35	V
		V _{CC} =6.0V		-	2.8	1.8	V
HIGH-level output voltage	V _{OH}	V _I =V _{IH} or V _{IL}	I _O =-20uA; V _{CC} =2.0V	1.9	2.0	-	V
			I _O =-20uA; V _{CC} =4.5V	4.4	4.5	-	V
			I _O =-20uA; V _{CC} =6.0V	5.9	6.0	-	V
			I _O =-6.0mA; V _{CC} =4.5V	3.98	4.32	-	V
			I _O =-7.8mA; V _{CC} =6.0V	5.48	5.81	-	V
LOW-level output voltage	V _{OL}	V _I =V _{IH} or V _{IL}	I _O =20uA; V _{CC} =2.0V	-	0	0.1	V
			I _O =20uA; V _{CC} =4.5V	-	0	0.1	V
			I _O =20uA; V _{CC} =6.0V	-	0	0.1	V
			I _O =6.0mA; V _{CC} =4.5V	-	0.15	0.26	V
			I _O =7.8mA; V _{CC} =6.0V	-	0.16	0.26	V
input leakage current	I _I	V _I =V _{CC} or GND; V _{CC} =6.0V		-	-	±1.0	uA
OFF-state output current	I _{OZ}	V _I =V _{IH} or V _{IL} ; V _{CC} =6.0V; V _O =V _{CC} or GND		-	-	±1.0	uA
supply current	I _{CC}	V _I =V _{CC} or GND; I _O =0A; V _{CC} =6.0V		-	-	8.0	uA
input capacitance	C _I	-		-	3.5	-	pF
input/output capacitance	C _{I/O}	-		-	10	-	pF

DC Characteristics 2

($T_{amb} = -40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
HIGH-level input voltage	V_{IH}	$V_{CC}=2.0V$		1.5	-	-	V
		$V_{CC}=4.5V$		3.15	-	-	V
		$V_{CC}=6.0V$		4.2	-	-	V
LOW-level input voltage	V_{IL}	$V_{CC}=2.0V$		-	-	0.5	V
		$V_{CC}=4.5V$		-	-	1.35	V
		$V_{CC}=6.0V$		-	-	1.8	V
HIGH-level output voltage	V_{OH}	$V_I=V_{IH}$ or V_{IL}	$I_O=-20\mu A; V_{CC}=2.0V$	1.9	-	-	V
			$I_O=-20\mu A; V_{CC}=4.5V$	4.4	-	-	V
			$I_O=-20\mu A; V_{CC}=6.0V$	5.9	-	-	V
			$I_O=-6.0mA; V_{CC}=4.5V$	3.84	-	-	V
			$I_O=-7.8mA; V_{CC}=6.0V$	5.34	-	-	V
LOW-level output voltage	V_{OL}	$V_I=V_{IH}$ or V_{IL}	$I_O=20\mu A; V_{CC}=2.0V$	-	-	0.1	V
			$I_O=20\mu A; V_{CC}=4.5V$	-	-	0.1	V
			$I_O=20\mu A; V_{CC}=6.0V$	-	-	0.1	V
			$I_O=6.0mA; V_{CC}=4.5V$	-	-	0.33	V
			$I_O=7.8mA; V_{CC}=6.0V$	-	-	0.33	V
input leakage current	I_I	$V_I=V_{CC}$ or GND; $V_{CC}=6.0V$		-	-	± 1.0	μA
OFF-state output current	I_{OZ}	$V_I=V_{IH}$ or $V_{IL}; V_{CC}=6.0V; V_O=V_{CC}$ or GND		-	-	± 5.0	μA
supply current	I_{CC}	$V_I=V_{CC}$ or GND; $I_O=0A; V_{CC}=6.0V$		-	-	80	μA

DC Characteristics 3

($T_{amb} = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
HIGH-level input voltage	V _{IH}	V _{CC} =2.0V		1.5	-	-	V
		V _{CC} =4.5V		3.15	-	-	V
		V _{CC} =6.0V		4.2	-	-	V
LOW-level input voltage	V _{IL}	V _{CC} =2.0V		-	-	0.5	V
		V _{CC} =4.5V		-	-	1.35	V
		V _{CC} =6.0V		-	-	1.8	V
HIGH-level output voltage	V _{OH}	V _I =V _{IH} or V _{IL}	I _O =-20uA; V _{CC} =2.0V	1.9	-	-	V
			I _O =-20uA; V _{CC} =4.5V	4.4	-	-	V
			I _O =-20uA; V _{CC} =6.0V	5.9	-	-	V
			I _O =-6.0mA; V _{CC} =4.5V	3.7	-	-	V
			I _O =-7.8mA; V _{CC} =6.0V	5.2	-	-	V
LOW-level output voltage	V _{OL}	V _I =V _{IH} or V _{IL}	I _O =20uA; V _{CC} =2.0V	-	-	0.1	V
			I _O =20uA; V _{CC} =4.5V	-	-	0.1	V
			I _O =20uA; V _{CC} =6.0V	-	-	0.1	V
			I _O =6.0mA; V _{CC} =4.5V	-	-	0.4	V
			I _O =7.8mA; V _{CC} =6.0V	-	-	0.4	V
input leakage current	I _I	V _I =V _{CC} or GND; V _{CC} =6.0V		-	-	±1.0	uA
OFF-state output current	I _{OZ}	V _I =V _{IH} or V _{IL} ; V _{CC} =6.0V; V _O =V _{CC} or GND		-	-	±10	uA
supply current	I _{CC}	V _I =V _{CC} or GND; I _O =0A; V _{CC} =6.0V		-	-	160	uA

AC Characteristics 1

($T_{amb} = 25^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit	
An to Bn or Bn to An propagation delay	t_{PLH}, t_{PHL}	see Figure 4	$V_{CC}=2.0V$	-	25	90	ns
			$V_{CC}=4.5V$	-	9	18	ns
			$V_{CC}=5.0V; C_L=15pF$	-	7	-	ns
			$V_{CC}=6.0V$	-	7	15	ns
$\bar{O}E$ to An or Bn enable time	t_{PZL}, t_{PZH}	see Figure 5	$V_{CC}=2.0V$	-	30	150	ns
			$V_{CC}=4.5V$	-	11	30	ns
			$V_{CC}=6.0V$	-	9	26	ns
$\bar{O}E$ to An or Bn disable time	t_{PLZ}, t_{PHZ}	see Figure 5	$V_{CC}=2.0V$	-	41	150	ns
			$V_{CC}=4.5V$	-	15	30	ns
			$V_{CC}=6.0V$	-	12	26	ns
transition time	t_{THL}, t_{TLH}	see Figure 4	$V_{CC}=2.0V$	-	14	60	ns
			$V_{CC}=4.5V$	-	5	12	ns
			$V_{CC}=6.0V$	-	4	10	ns

AC Characteristics 2

($T_{amb} = -40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
An to Bn or Bn to An propagation delay	t_{PLH}, t_{PHL}	see Figure 4	$V_{CC}=2.0\text{V}$	-	-	115 ns
			$V_{CC}=4.5\text{V}$	-	-	23 ns
			$V_{CC}=6.0\text{V}$	-	-	20 ns
$\bar{O}E$ to An or Bn enable time	t_{PZL}, t_{PZH}	see Figure 5	$V_{CC}=2.0\text{V}$	-	-	190 ns
			$V_{CC}=4.5\text{V}$	-	-	38 ns
			$V_{CC}=6.0\text{V}$	-	-	33 ns
$\bar{O}E$ to An or Bn disable time	t_{PLZ}, t_{PHZ}	see Figure 5	$V_{CC}=2.0\text{V}$	-	-	190 ns
			$V_{CC}=4.5\text{V}$	-	-	38 ns
			$V_{CC}=6.0\text{V}$	-	-	33 ns
transition time	t_{THL}, t_{TLH}	see Figure 4	$V_{CC}=2.0\text{V}$	-	-	75 ns
			$V_{CC}=4.5\text{V}$	-	-	15 ns
			$V_{CC}=6.0\text{V}$	-	-	13 ns

AC Characteristics 3

($T_{amb} = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
An to Bn or Bn to An propagation delay	t_{PLH}, t_{PHL}	see Figure 4	$V_{CC}=2.0\text{V}$	-	-	135 ns
			$V_{CC}=4.5\text{V}$	-	-	27 ns
			$V_{CC}=6.0\text{V}$	-	-	23 ns
$\bar{O}E$ to An or Bn enable time	t_{PZL}, t_{PZH}	see Figure 5	$V_{CC}=2.0\text{V}$	-	-	225 ns
			$V_{CC}=4.5\text{V}$	-	-	45 ns
			$V_{CC}=6.0\text{V}$	-	-	38 ns
$\bar{O}E$ to An or Bn disable time	t_{PLZ}, t_{PHZ}	see Figure 5	$V_{CC}=2.0\text{V}$	-	-	225 ns
			$V_{CC}=4.5\text{V}$	-	-	45 ns
			$V_{CC}=6.0\text{V}$	-	-	38 ns
transition time	t_{THL}, t_{TLH}	see Figure 4	$V_{CC}=2.0\text{V}$	-	-	90 ns
			$V_{CC}=4.5\text{V}$	-	-	18 ns
			$V_{CC}=6.0\text{V}$	-	-	15 ns

Testing Circuit

AC Testing Circuit




Figure 3. Test circuit for measuring switching times

Definitions for test circuit: R_L =Load resistance.

C_L =Load capacitance including jig and probe capacitance.

R_T =Termination resistance should be equal to the output impedance Z_o of the pulse generator. S1=Test selection switch.

AC Testing Waveforms




Figure 4. Input (An, Bn) to output (Bn, An) propagation delays and output transition times




Figure 5. 3-state enable and disable times

Measurement Points

Type	Input	Output
	V_M	V_M
SN74HC245	$0.5 \times V_{CC}$	$0.5 \times V_{CC}$




Test Data

Type	Input		Load		S1 position		
	V _I	t _r ,t _f	C _L	R _L	t _{PHL} , t _{PLH}	t _{PZH} , t _{PHZ}	t _{PZL} , t _{PLZ}
SN74HC245	V _{CC}	6ns	15pF, 50pF	1kΩ	open	GND	V _{CC}

Package Information




· DIP-20

Symbol	Size	Dimensions In Millimeters		Symbol	Size	Dimensions In Inches	
		Min (mm)	Max (mm)			Min (in)	Max (in)
A		3.600	5.330	A		0.142	0.210
A1		0.510		A1		0.020	
A2		3.200	3.600	A2		0.126	0.142
B		0.360	0.530	B		0.014	0.021
B1		1.52 (BSC)		B1		0.060 (BSC)	
c		0.204	0.360	c		0.008	0.014
D		25.70	26.54	D		1.010	1.040
E1		6.200	6.750	E1		0.244	0.260
E2		7.620	9.300	E2		0.300	0.366
e		2.54 (BSC)		e		0.100 (BSC)	
L		3.000	3.600	L		0.118	0.142




• S01C-20-208mil

Size Symbol	Dimensions In Millimeters		Size Symbol	Dimensions In Inches	
	Min (mm)	Max (mm)		Min (in)	Max (in)
A		2.000	A		0.079
A1	0.050	0.250	A1	0.002	0.010
A2	1.650	1.850	A2	0.065	0.073
b	0.350	0.550	b	0.014	0.022
c	0.150	0.200	c	0.006	0.008
D	12.25	12.65	D	0.482	0.498
E	7.600	8.000	E	0.299	0.315
E1	5.100	5.500	E1	0.201	0.217
e	1.270		e	0.050	
L	0.550	0.950	L	0.022	0.037
L1	1.250		L1	0.049	
θ	0°	8°	θ	0°	8°





▪ SOP-20

Symbol \ Size	Dimensions In Millimeters		Symbol \ Size	Dimensions In Inches	
	Min(mm)	Max(mm)		Min(in)	Max(in)
A	2.470	2.650	A	0.097	0.104
A1	0.050	0.300	A1	0.002	0.012
A2	2.200	2.440	A2	0.087	0.096
b	0.350	0.500	b	0.014	0.020
c	0.150	0.300	c	0.006	0.012
D	12.54	12.94	D	0.494	0.509
E	10.00	10.60	E	0.394	0.417
E1	7.300	7.700	E1	0.287	0.303
e	1.270 (BSC)		e	0.050 (BSC)	
L	0.400	1.050	L	0.016	0.041
L1	1.300	1.500	L1	0.051	0.059
θ	0°	8°	θ	0°	8°



· TSSOP-20

Symbol	Dimensions In Millimeters		Symbol	Dimensions In Inches	
	Min(mm)	Max(mm)		Min(in)	Max(in)
D	6.400	6.600	D	0.252	0.259
E	4.300	4.500	E	0.169	0.177
b	0.190	0.300	b	0.007	0.012
c	0.090	0.200	c	0.004	0.008
E1	6.250	6.550	E1	0.246	0.258
A		1.200	A		0.047
A2	0.800	1.000	A2	0.031	0.039
A1	0.050	0.150	A1	0.002	0.006
e	0.65 (BSC)		e	0.026 (BSC)	
L	0.500	0.700	L	0.020	0.028
H	0.25 (TYP)		H	0.01 (TYP)	
θ	1°	7°	θ	1°	7°



Statement

- XBLW reserves the right to modify the product manual without prior notice! Before placing an order, customers need to confirm whether the obtained information is the latest version and verify the completeness of the relevant information.
- Any semi-guide product is subject to failure or malfunction under specified conditions. It is the buyer's responsibility to comply with safety standards when using XBLW products for system design and whole machine manufacturing. And take the appropriate safety measures to avoid the potential in the risk of loss of personal injury or loss of property situation!
- XBLW product has not been licensed for life support, military and aerospace applications, and therefore XBLW is not responsible for any consequences arising from its use in these areas.
- If any or all XBLW products (including technical data, services) described or contained in this document are subject to any applicable local export control laws and regulations, they may not be exported without an export license from the relevant authorities in accordance with such laws.
- The specifications of any and all XBLW products described or contained in this document specify the performance, characteristics, and functionality of said products in their standalone state, but do not guarantee the performance, characteristics, and functionality of said products installed in Customer's products or equipment. In order to verify symptoms and conditions that cannot be evaluated in a standalone device, the Customer should ultimately evaluate and test the device installed in the Customer's product device.
- XBLW documentation is only allowed to be copied without any alteration of the content and with the relevant authorization. XBLW assumes no responsibility or liability for altered documents.
- XBLW is committed to becoming the preferred semiconductor brand for customers, and XBLW will strive to provide customers with better performance and better quality products.